

Black STEEL

Black Steel blanks are built from longitudinal 120g graphite carbon fiber, E-type fiberglass, and a proprietary resin bonding system that allows us to combine the two materials without fear of de-lamination. Our Black Steel blanks have been the standard in the industry. They have slightly softer actions to accommodate the use of braided lines with short top-shots but have the pulling power to stop the hardest fighting fish swimming.

Unlike other composite blank manufacturers, we have an extensive lineup of different actions that meet the needs of the most discerning fishermen. There are a number of models that aren't even built into our seeker finished rod lineup. Those are reserved for the fisherman who is looking for that specialty rod that no one else has.

Black Steel blanks use a polyurethane* high gloss coating with UV inhibitors. This coating has been found to be the most durable and the most long lasting of any that have been used in the past.



System #	Model #	Line Rating	Length	Tip Size	Butt Size	Finished Rod Equivalent
12210801	CLB602	8-12	6'	6	.620	
12215801	CLB604	8-12	6'	6.5	.640	
12220801	CLB606	12-20	6'	7	.680	
12230801	CLB702	8-15	7'	6	.700	
12245881	CLBF704	10-15	7'	6	.800	G196-7
12245891	CLBF706	12-20	7'	6.5	.835	G270-7
12245901	CLBF708	15-25	7'	7	.860	G870-7
12250801	CLB804	10-25	8'	6.5	.770	G196-8
12253801	CLB806	12-30	8'	7	.775	G270-8
12255801	CLB806H	15-40	8'	8	.780	G270H-8
12610801	CSB807	20-30	8'	9	.785	
12613801	CSB907	20-30	9'	9	.860	
12615801	CSB909	25-50	9'	10	.940	
12410801	CJB60XF	15-40	6'	6.5	.940	G660XF-6
12415801	CJB60	20-40	6'	9	.740	G660-6
12420801	CJB65F	15-40	6'6"	7	.925	G665F-6 1/2
12425801	CJB65	20-40	6'6"	9	.775	G665-6 1/2
12422801	CJB65H	30-80	6'6"	10	.855	G665H-6 1/2
12450801	CJB70F	20-40	7'	7	.975	G970-7
12430801	CJB70	20-50	7'	9	.790	G670-7
12435801	CJB70H	30-80	7'	10	.875	G670H-7
12450901	CJB80F	20-30	8'	7	1.000	G980-8
12440801	CJB80H	30-80	8'	10	.920	
12450911	CJB90F	20-30	9'	7	1.20	
12451801	CJBF60	20-40	6'	8	.740	G6460-6
12451901	CJBF60H	40-60	6'	8	1.000	G6460H-6
12452801	CJBF65	20-40	6'6"	8	1.015	G6465-6 1/2
12422901	CJBF65H	30-50	6'6"	11	1.050	G6465H-6 1/2
12465801	CJBF65XH	30-80	6'6"	12	1.050	G6465XH-6 1/2
12441801	CJBF70	30-50	7'	9	1.080	G6470-7
12442801	CJBF70M	25-40	7'	8	.985	
12442901	CJBF70H	40-60	7'	11	1.100	G6470H-7
12443901	CJBF70XH	50-80	7'	12	1.125	G6470XH-7
12453801	CJBF80	20-40	8'	9	1.145	G6480-8
12454801	CJBF80H	30-50	8'	9	1.160	G6480H-8
12454901	CJBF80XH	40-60	8'	10	1.210	G6480XH-8
12460801	CJBF85	25-40	8'6"	11	1.020	G6485-8 1/2
12463801	CJBF90M	25-50	9'	9	1.125	G6490-9
12464801	CJBF100 (NEW)	25-40	10'	10	1.250	G6500-10 (NEW)
12552801	CTS F50XXH	60-100	5'	14	.900	
12545801	CTS55H	30-80	5'6"	10	.830	
12550801	CTS55XH	40-60	5'6"	12	.825	G655XH-5 1/2
12554801	CTS F55XH	50-80	5'6"	12	.875	G6455XH-5 1/2
12555801	CTS F55XXH	60-100	5'6"	14	.930	G6455XXH-5 1/2
12556101	CTS F55XXXH	80-130	5'6"	16	.950	G6455XXXH-5 1/2
12560801	CTS60H	30-60	6'	10	.830	G660H-6
12565801	CTS60XH	40-100	6'	12	.855	G660XH-6
12556801	CTS F60XH	50-80	6'	12	1.060	G6460XH-6
12557801	CTS F60XXH	60-130	6'	14	1.060	G6460XXH-6
12557901	CTS F60XXXH	80-130	6'	16	.945	G6460XXXH-6
12552901	CTS F63XXH	60-100	6'3"	14	1.100	G6463XXH-6 1/4
12558001	CTS F63XXXH	80-130	6'3"	14	1.00	G6463XXXH-6 1/4
12558101	CTS F63XXXXH	80-150	6'3"	16	1.100	G6463XXXXH-6 1/4



*-Polyurethane coatings require the use of denatured alcohol during the clean up of the blank in lieu of the traditional acetone. Acetone is a polyurethane dilutant and will breakdown the finish of the blank. Please take note as our warranty does not cover the finish and the use of acetone.