



VSYSTEM

- DFD: Precision Dual Force Drag system
- Multi-disk, Japanese oiled felt drag washers
- Up to 15 stainless steel ball bearings
- E2BB and HPB corrosion resistant bearings
- 1 Quick-Set Anti-Reverse roller bearing
- Precision machine cut brass pinion gear
- Precision cut hardened brass alloy main gear
- ALC: Rigid diecast aluminum frame, sideplate & rotor
- Patented Elliptical Oscillation System
- Spare matching aluminum spool with DFD
- Rigid forged aluminum screw-in handle design
- Ergo Grip handle knobs on 40 sized reels and larger
- Hydro Block water tight drag seal
- Oversized aluminum bail wire
- 5-year Okuma backed warranty program

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
OKUV15A	5.0:1	12BB+1RB	8.0	20"	2/240, 4/130, 6/80	\$124.44	\$111.99
OKUV20A	5.0:1	12BB+1RB	9.4	22"	4/190, 6/110, 8/90	124.44	111.99
OKUV30A	5.0:1	15BB+1RB	11.6	25"	6/200, 160/8, 10/110	132.21	118.99
OKUV40A	5.0:1	15BB+1RB	12.4	26"	8/270, 10/190, 12/170	132.21	118.99
OKUV55A	4.5:1	15BB+1RB	16.5	30"	10/380, 12/340, 15/240	132.21	118.99
OKUV65A	4.8:1	15BB+1RB	23.2	34"	12/430, 15/310, 20/260	155.55	139.99



EPIXOR

- Multi-disk, Japanese oiled felt drag washers
- 9 stainless steel ball bearings
- 1 Quick-Set Anti-Reverse roller bearing
- Precision machine cut brass pinion gear
- ALC: Rigid diecast aluminum frame
- Patented Elliptical Oscillation System
- Spare anodized aluminum spool
- Rigid forged aluminum handle design
- Hydro Block water tight drag seal
- Oversized aluminum bail wire
- Narrow Blade Body design

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
OKUEF15A	5.0:1	9BB+1RB	7.9	20"	2/240, 4/130, 6/80	\$46.50	\$41.85
OKUEF20A	5.0:1	9BB+1RB	8.3	22"	4/190, 6/110, 8/90	46.50	41.85
OKUEF30A	5.0:1	9BB+1RB	10.1	25"	6/200, 160/8, 10/110	53.66	48.29
OKUEF40A	5.0:1	9BB+1RB	11.2	28"	8/270, 10/190, 12/170	53.66	48.29
OKUEF55A	5.0:1	9BB+1RB	15.5	30"	10/380, 12/340, 15/240	53.66	48.29
OKUEF65A	5.0:1	9BB+1RB	21.6	34"	12/430, 15/310, 20/260	60.82	54.73



EPIXOR EB SERIES

- Multi-disk, Japanese oiled felt drag washers
- EDS: Extra Drag Surface spool design
- 9 stainless steel ball bearings
- 1 Quick-Set Anti-Reverse roller bearing
- Precision machine cut brass pinion gear
- Rigid forged aluminum handle design
- Patented on/off auto trip bait feeding action
- Hydro Block water tight drag seal

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
OKUEB20	5.0:1	9BB+1RB	11.6	25"	4/290, 6/180, 8/140	\$57.24	\$51.51
OKUEB30	5.0:1	9BB+1RB	12.2	27"	6/330, 8/260, 10/180	64.39	57.95
OKUEB50	4.5:1	9BB+1RB	17.4	31"	10/440, 12/390, 15/280	64.39	57.95
OKUEB65	4.5:1	9BB+1RB	26.7	36"	12/540, 15/390, 20/320	71.55	64.39
OKUEB80	4.5:1	9BB+1RB	28.1	40"	15/510, 20/420, 25/310	71.55	64.39



SALINA

- DFD: Precision Dual Force Drag system
- Multi-disk, Japanese oiled felt drag washers
- 4 HPB corrosion resistant stainless bearings
- 1 Quick-Set Anti-Reverse roller bearing
- Precision machine cut brass pinion gear
- Precision cut "High Density Gearing"
- ALC: Rigid diecast aluminum frame, sideplate & rotor
- Patented Elliptical Oscillation System
- Rigid forged aluminum screw-in handle design
- Hydro Block water tight drag seal
- Oversized aluminum bail wire
- Narrow Blade Body design

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
OKUSA30	5.0:1	4BB+1RB	10.1	25"	6/200, 8/160, 10/110	\$77.77	\$69.99
OKUSA40	5.0:1	4BB+1RB	11.1	28"	8/270, 10/190, 12/170	77.77	69.99
OKUSA45	4.5:1	4BB+1RB	15.0	26"	10/240, 12/210, 15/150	85.55	76.99
OKUSA55	4.5:1	4BB+1RB	15.4	30"	10/380, 12/340, 15/240	85.55	76.99
OKUSA65	4.8:1	4BB+1RB	21.5	34"	12/430, 15/310, 20/260	93.33	83.99
OKUSA80	4.8:1	4HPB	21.9	38"	15/420, 20/350, 25/260	93.33	83.99





AVENGER

- Multi-disk, Japanese-oiled felt drag washers
- 1 Quick set anti-reverse roller bearing
- Spare graphite spool
- 6 ball bearings for ultimate smoothness
- Precision machine-cut brass pinion gear
- Hydro Block water-tight drag seal
- Patented Elliptical Oscillation System

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
OKUAV15A	5.0:1	6BB+1RB	7.3	20"	2/240, 4/130, 6/80	\$25.04	\$22.53
OKUAV20A	5.0:1	6BB+1RB	7.8	22"	4/190, 6/110, 8/90	25.04	22.53
OKUAV30A	5.0:1	6BB+1RB	9.7	25"	6/200, 8/160, 10/110	28.62	25.75
OKUAV40A	5.0:1	6BB+1RB	10.3	28"	8/270, 10/190, 12/170	28.62	25.75
OKUAV55A	4.5:1	6BB+1RB	14.5	30"	10/380, 12/340, 15/240	32.19	28.97
OKUAV65A	4.8:1	6BB+1RB	20.9	34"	12/430, 15/310, 20/260	39.35	35.41
OKUAV80A	4.8:1	6BB+1RB	21.4	38"	15/420, 20/350, 25/260	39.35	35.41



AVENGER ABF

- Patented On/Off auto-trip baitfeeding function
- 1 Quick-set anti-reverse roller bearing
- Aluminum handle knobs on 40-80 sizes
- Multi-disk, Japanese-oiled felt drag washers
- Precision machine cut brass pinion gear
- Hydro Block water-tight drag seal
- 6 stainless steel ball bearings
- Rigid, diecast-aluminum handle design
- Spare G-Tech spool system

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
OKUABF40	4.5:1	6BB+1RB	16.3	28"	8/410, 10/290, 12/260	\$35.77	\$32.19
OKUABF50	4.5:1	6BB+1RB	17.3	31"	10/440, 12/390, 15/280	39.35	35.41
OKUABF65	4.5:1	6BB+1RB	27.4	36"	12/540, 15/390, 20/320	46.50	41.85
OKUABF90	4.5:1	6BB+1RB	27.6	40"	20/590, 25/440, 30/330	46.50	41.85



CORONADO

- Three sealed stainless steel ball bearings
- One-touch lever-clutch baitfeeder system
- Forged-aluminum handle
- Quick-set anti-reverse one-way bearing
- Gasket-sealed drag system
- Patented micro-adjustable baitfeeder drag
- Stainless steel drive gear and pinion gear

No.	Gear Ratio	Bearings	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
OKUCD50	4.5:1	3BB+1RB	31"	10/330, 12/290, 15/210	\$57.24	\$51.51
OKUCD65	4.5:1	3BB+1RB	36"	12/440, 15/310, 20/260	64.33	57.95
OKUCD90	4.5:1	3BB+1RB	40"	20/590, 25/440, 30/240	64.33	57.95



IGNITE

- Multi-disk, Japanese-oiled felt drag washers
- Precision machine cut brass pinion gear
- Machined-aluminum anodized spool
- 4 ball bearings for ultimate smoothness
- Patented Elliptical Oscillation System
- 1 Quick-set anti-reverse roller bearing
- Hydro Block water-tight drag seal

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
OKUIT10	5.0:1	4BB+1RB	5.9	20"	2/270, 4/140, 6/90	\$21.46	\$19.31
OKUIT20	5.0:1	4BB+1RB	7.7	22"	4/190, 6/110, 8/90	25.04	22.53
OKUIT30	5.0:1	4BB+1RB	9.4	25"	6/200, 8/160, 10/110	25.04	22.53
OKUIT40	5.0:1	4BB+1RB	10.2	28"	8/270, 10/190, 12/170	25.04	22.53
OKUIT55	4.5:1	4BB+1RB	14.6	30"	10/380, 12/340, 15/240	32.19	28.97
OKUIT65	4.8:1	4BB+1RB	21.6	34"	12/430, 15/310, 20/260	32.19	28.97
OKUIT80	4.8:1	4BB+1RB	22.2	38"	15/420, 20/350, 25/260	32.19	28.97



SALINA BAIT FEEDER

- Patented On/Off auto-trip bait feeding function
- 4 HPB corrosion-resistant stainless bearings
- ALC: Rigid, diecast-aluminum screw-in handle design
- Blade Body design
- DFD: Precision Dual Force Drag system
- 1 Quick-set anti-reverse roller bearing
- Hydro Block water-tight drag seal
- Multi-Disk, Japanese-oiled felt drag washers
- Precision cut "High Density Gearing"
- Oversized, solid aluminum bail wire

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
OKUSAF55	4.5:1	4HPB+1RB	18.7	30"	10/380, 12/340, 15/240	\$108.88	\$97.99
OKUSAF65	4.8:1	4HPB+1RB	26.2	34"	12/430, 15/310, 20/260	116.66	104.99
OKUSAF80	4.8:1	4HPB+1RB	27.5	38"	15/420, 20/350, 25/260	116.66	104.99





TRAVERTINE

- Multi-disk, Japanese oiled felt drag washers
- 4 ball bearings for ultimate smoothness
- Precision machine cut brass pinion gear
- Hydro Block water tight drag seal
- 1 Quick-Set Anti-Reverse roller bearing
- Patented Elliptical Oscillation System
- Machined aluminum anodized spool

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
OKUTR15	5.0:1	4BB+1RB	7.6	20"	2/240, 4/130, 6/80	\$19.31	\$17.38
OKUTR20	5.0:1	4BB+1RB	7.8	22"	4/190, 6/110, 8/90	19.31	17.38
OKUTR30	5.0:1	4BB+1RB	8.7	25"	6/220, 8/160, 10/110	21.46	19.31
OKUTR40	4.5:1	4BB+1RB	8.9	28"	8/270, 10/190, 12/170	21.46	19.31
OKUTR45	4.5:1	4BB+1RB	11.7	26"	10/240, 12/340, 15/240	25.04	22.53
OKUTR55	4.5:1	4BB+1RB	13.1	30"	10/380, 12/340, 15/240	25.04	22.53



INDURON IDX

- Titanium coated line guide insert
- Precision machine cut brass gears
- Adjustable 6-pin Velocity Control System
- Engaged levelwind on 250/400 models
- Multi-disk Carbonite drag washers
- 1-piece Machined Rigid Frame construction
- Inertia free Hi-Rise spool on IDx-150
- 7 stainless steel ball bearings
- 1 Quick-Set Anti-Reverse roller bearing

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
OKUIDX150A	5.1:1	7BB+1RB	11.5	22"	6/260, 8/210, 10/150	\$101.10	\$90.99
OKUIDX250A	5.1:1	7BB+1RB	12.0	22"	8/380, 10/270, 15/170	101.10	90.99
OKUIDX400A	5.1:1	7BB+1RB	13.1	22"	14/270, 18/210, 20/180	101.10	90.99



CATALINA

- Strong Arm levelwind: Ti coated
- Dual anti-reverse feature on all sizes
- 1-piece Machined Rigid Frame construction
- Machined aluminum silver anodized spools
- Multi-disk Rulidium drag system
- Durable stainless steel XL gearing system
- Ergo grip handle knobs on all sizes
- Spool stabilizing system for improved freespool
- Micro-click drag adjustment system
- Self Lubricating Gear System on all sizes
- SLG: Speed loc pinion gear system on all sizes

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
LEVELWIND REELS							
OKUCT15L	5.1:1	3BB+1RB	16.8	23"	10/330, 12/290, 14/240	\$101.10	\$90.99
OKUCT25L	4.0:1	3BB+1RB	21.3	24"	15/390, 20/320, 25/230	108.88	97.99
OKUCT30L	4.0:1	3BB+1RB	22.1	24"	15/510, 20/420, 25/310	108.88	97.99
OKUCT45L	4.0:1	3BB+1RB	24.3	26"	20/580, 25/430, 30/330	108.88	97.99
CASTING & TROLLING							
OKUCT25CS	6.2:1	3BB+1RB	20.0	37"	15/390, 20/320, 25/230	101.10	90.99
OKUCT30CS	6.2:1	3BB+1RB	24.0	37"	15/510, 20/420, 25/310	101.10	90.99
OKUCT45C	4.0:1	3BB+1RB	23.2	26"	20/580, 25/430, 30/330	108.88	97.99
OKUCT55N	6.2:1	3BB+1RB	28.5	53"	25/470, 30/360, 40/310	116.66	104.99



CONVECTOR

- Ti coated Strong Arm levelwind
- Durable stainless steel XL gearing system
- line counters)
- freespool
- Multi-disk CARBONITE drag washers
- Self Lubricating Gear System on all sizes
- Machined aluminum silver anodized spools
- Stainless steel Body Armor on all 55 sized reels
- 2 stainless steel ball bearings
- Ergo grip handle knobs on all sizes
- Stainless steel spool version on CV-55SS
- 1 Quick-Set Anti-Reverse roller bearing
- SLG: Speed loc pinion gear (excludes line counters)
- Spool stabilizing system for improved
- Dual anti-reverse feature on all sizes

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
OKUCV30L	4.0:1	2BB+1RB	20.9	24"	15/510, 20/420, 25/310	\$57.24	\$51.51
OKUCV45L	4.0:1	2BB+1RB	22.4	26"	20/580, 25/430, 30/330	60.82	54.73
OKUCV55L	4.0:1	2BB+1RB	34.7	34"	25/470, 30/360, 40/310	71.55	64.39



CONTOURA

- Lightweight, corrosion-resistant graphite frame
- Magnetic cast-control system
- Quick set anti-reverse roller bearing
- Machined-aluminum anodized spool
- Multi-disk Carbonite drag system
- Speed Lock pinion gear system
- Oversized, stainless XL gearing system
- 2BB+1RB Stainless bearing drive system

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
OKUCR203CS	7.1:1	2BB+1RB	15.6	32"	14/290, 18/230, 20/210	\$77.77	\$69.99
OKUCR303CS	6.2:1	2BB+1RB	19.9	37"	15/510, 20/420, 25/310	85.55	76.99
OKUCR453CS	6.2:1	2BB+1RB	22.0	41"	20/580, 430/25, 30/330	93.33	83.99





CLASSIC/CLASSIC PRO

- 2 stainless steel ball bearings on Pro model
- Graphite bushings on standard Classic model
- Machine cut brass and stainless steel gearing
- XL gearing system on all 55 sized reels
- Self Lubricating Gear System on all sizes
- 1-piece corrosion resistant graphite frames
- Corrosion resistant graphite spools

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
OKUCL202L	5.1:1	2BB	11.2	23"	14/290, 18/230, 20/210	\$28.62	\$25.75
OKUCL302L	4.0:1	2BB	15.9	24"	15/510, 20/420, 25/310	28.62	25.75
CLASSIC STAR DRAG REELS							
OKUCL200L	5.1:1	2BB	11.2	23"	14/290, 18/230, 20/210	25.04	22.53
OKUCL300L	4.0:1	2BB	15.9	24"	15/510, 20/420, 25/310	25.04	22.53
OKUCL450L	4.0:1	2BB	17.3	26"	20/580, 25/430, 30/330	25.04	22.53



TITUS GOLD

- Carbonite: heat resistant drag washers
- XL gearing on all high-speed "S" models
- 2-speed gearing on all "II" designated models
- Machine cut stainless steel gears on all sizes
- 4 to 5 stainless steel HPB ball bearings
- Double pawl silent anti-reverse system
- Ergo Grip handle knobs on 10/15II and S models
- ACG: Comfort grip knobs on 20-50W 2-speeds
- 1-piece machined Rigid Frame construction
- Cold forged silver anodized aluminum spools
- Hippo Grip: Multi-purpose clamp for 50/50W
- Oversized stainless steel On/Off clicker ratchet
- 5-year Okuma backed warranty program

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
HIGH SPEED REELS							
OKUTG10S	6.2:1	5BB	24.3	41"	15/460, 20/380, 25/280	\$245.61	\$221.05
OKUTG15S	6.2:1	5BB	29.5	41"	20/550, 25/410, 30/310	245.61	221.05
OKUTG20S	6.2:1	5BB	30.5	50"	25/620, 30/480, 40/400	270.17	243.15



MAGDA PRO

- Multi-disk Carbonite drag washers
- 2 stainless steel ball bearings
- Machine-cut brass gearing
- Self-lubricating gear system
- Corrosion-resistant graphite spools
- Strike zone line counter measures in feet

No.	Gear Ratio	Bearings	Weight (oz.)	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
LINE COUNTER REELS							
OKUMA15DX	5.1:1	2BB	13.2	23"	330/10, 290/12, 240/14	\$32.19	\$28.97
OKUMA20DX	5.1:1	2BB	13.8	23"	290/14, 230/18, 210/20	32.19	28.97
OKUMA30DX	4.0:1	2BB	17.3	24"	510/15, 420/20, 310/25	35.77	32.19
OKUMA45DX	4.0:1	2BB	18.6	26"	580/20, 430/25, 330/30	39.35	35.41
LEFT HANDED LINE COUNTER REELS							
OKUMA20DLX	5.1:1	2BB	13.8	22"	290/14, 230/18, 210/20	32.19	28.97
OKUMA30DLX	4.0:1	2BB	17.3	24"	510/15, 420/20, 310/25	35.17	32.19



TITUS

- Strong Arm levelwind: Ti coated on T-20L
- Oversized stainless steel and composite drag system
- 2-speed gearing on all "II" designated models
- Machine cut stainless steel gears on all sizes
- 4 stainless steel ball bearings
- Double pawl silent anti-reverse system on 20/30
- Powerful aluminum handle knobs on all sizes
- Heavy duty stainless steel handle arms
- Corrosion resistant graphite frames
- Cold forged silver anodized aluminum spools
- Oversized stainless steel On/Off clicker ratchet

No.	Gear Ratio	Bearings	Line Retrieve	Monofilament Line Capacity	Price	10% Discount
LEVELWIND REELS						
OKUT20L	3.5:1	4BB	29"	25/570, 30/470, 40/400	114.48	103.03
SINGLE-SPEED REELS						
OKUT20	3.5:1	4BB	29"	25/570, 30/470, 40/400	100.17	90.15
OKUT30	3.5:1	4BB	29"	30/630, 40/530, 50/390	107.33	96.59
OKUT50	3.1:1	4BB	30"	30/830, 50/510, 80/300	114.48	103.03
OKUT50W	3.1:1	4BB	30"	50/710, 60/540, 80/420	121.64	109.47
TWO-SPEED REELS						
OKUT20II	3.8:1	4BB	31 & 14"	25/570, 30/470, 40/400	135.95	122.35
OKUT30II	3.5:1	4BB	31 & 14"	30/630, 40/530, 50/390	143.10	128.79





OKUMA FLY REELS

HELIOS

- Maintenance-free waterproof drag system
- 2B B + 1RB stainless steel bearing drive system
- Machined aluminum large arbor spool design 7/8 and 8/9 with full caged frame system

- Multi-disk cork and stainless drag washers
- Precision machined stainless steel spool shafts
- Non-slip positive grip rubberized handle knobs

- Roller bearing engages drag in one direction
- Anodized aluminum Machined Rigid Frame
- Easy-to-change left to right hand retrieval conversion

No.	Line Weight	Weight	Bearings	Line Retrive	Fly Line Cap.	Frame	Spool	Spool Width	Spool Diam.	Price	10% Discount
OKUH34	3,4 wt.	4.5	2BB + 1RB	8"	WF-3, 105 yds / 12 lbs	AL	AL	22mm	68mm	\$139.99	\$125.99
OKUH45	4,5 wt.	5.0	2BB + 1RB	9"	WF-4, 110 yds / 20 lbs	AL	AL	24mm	75mm	139.99	125.99
OKUH56	5,6 wt.	5.3	2BB + 1 RB	10"	WF-5, 130 yds / 20 lbs	AL	AL	28mm	82mm	139.99	125.99
OKUH78A	7,8 wt.	5.9	2BB + 1RB	11"	WF-7, 150 yds / 20 lbs	AL	AL	31mm	88mm	147.77	132.99
OKUH89A	8,9 wt.	6.2	2BB + 1RB	12"	WF-8, 250 yds / 20 lbs	AL	AL	34mm	95mm	147.77	132.99



VASHON

- Multi-disk cork and stainless drag washers
- Precision machined stainless steel spool shafts
- Non-slip positive grip rubberized handle knobs

- Roller bearing engages drag in one direction
- Anodized aluminum Machined Rigid Frame
- Easy to change left to right hand retrieval conversion

- Precision machined brass bushing drive system
- Machined aluminum mid arbor spool design

No.	Line Weight	Weight	Bearings	Line Retrive	Fly Line Cap.	Frame	Spool	Spool Width	Spool Diam.	Price	10% Discount
OKUV34	3,4 wt.	4.4	1RB	8"	WF-3, 70 yds / 20 lbs	AL	AL	26mm	65mm	\$85.86	\$77.27
OKUV56	5,6 wt.	5.0	1RB	9"	WF-5, 210 yds / 20 lbs	AL	AL	29mm	76mm	85.86	77.27
OKUV78	7,8 wt.	5.1	1RB	9"	WF-7, 160 yds / 20 lbs	AL	AL	29mm	79mm	85.86	77.27



MAGNITUDE

- Multi-disk Rulidium or Teflon drag washers
- Precision machined stainless steel spool shafts
- Both larger arbor and standard arbor spool designs

- Roller bearing engages drag in one direction
- Lightweight magnesium frame and spool design

- Precision machined brass bushing drive system
- Easy to change L to R hand retrieval conversion

No.	Line Weight	Weight	Bearings	Line Retrive	Fly Line Cap.	Frame	Spool	Spool Width	Spool Diam.	Price	10% Discount
OKUMD45	4,5 wt.	3.7	1RB	8"	WF-4, 105 yds / 12 lbs	MG	MG	17mm	67mm	\$39.35	\$35.42
OKUMD56	5,6 wt.	3.9	1RB	9"	WF-5, 160 yds / 20 lbs	MG	MG	20mm	73mm	39.35	35.42
OKUMD78	7,8 wt.	4.1	1RB	8"	WF-7, 75 yds / 20 lbs	MG	MG	24mm	67mm	39.35	35.42



SLV

- Multi-disk cork and stainless drag washers
- Precision machined stainless steel spool shafts
- Non-slip positive grip rubberized handle knobs

- Roller bearing engages drag in one direction
- ALC: Alumilite diecast aluminum frame design
- Easy to change left to right hand retrieval conversion

- Precision machined brass bushing drive system
- Diecast aluminum super large arbor spool design

No.	Line Weight	Weight	Bearings	Line Retrive	Fly Line Cap.	Frame	Spool	Spool Width	Spool Diam.	Price	10% Discount
OKUSLV23	2,3 wt.	4.5	1RB	8"	WF-2, 50 yds / 12 lbs	AL	AL	22mm	66mm	\$42.93	\$38.64
OKUSLV45	4,5 wt.	4.8	1RB	9"	WF-4, 95 yds / 12 lbs	AL	AL	24mm	75mm	42.93	38.64
OKUSLV56	5,6 wt.	5.3	1RB	10"	WF-5, 140 yds / 20 lbs	AL	AL	28mm	82mm	42.93	38.64
OKUSLV78	7,8 wt.	5.5	1RB	11"	WF-7, 145 yds / 20 lbs	AL	AL	31mm	88mm	42.93	38.64
OKUSLV89	8,9 wt.	6.1	1RB	12"	WF-8, 150 yds / 30 lbs	AL	AI	34mm	95mm	42.93	38.64



INTEGRITY "A" SERIES

- 5/6 & 7/8 with multi-disk Rulidium drag washers
- Precision machined brass bushing drive system
- Diecast aluminum super large arbor spool design

- 8/9 & 10/11 with multi-disk cork drag washers
- Precision machined stainless steel spool shafts
- Easy to change left to right hand retrieval conversion

- Roller bearing engages drag in one direction
- ALC: Alumilite diecast aluminum frame design

No.	Line Weight	Weight	Bearings	Line Retrive	Fly Line Cap.	Frame	Spool	Spool Width	Spool Diam.	Price	10% Discount
OKUI56	5,6 wt.	7.0	1RB	9"	WF-5, 70 yds / 12 lbs	AL	AL	25MM	76MM	\$46.50	\$41.85
OKUI78	7,8 wt.	7.5	1RB	9"	WF-7, 50 yds / 20 lbs	AL	AL	30mm	76mm	46.50	41.85
OKUI89	8,9 wt.	8.0	1RB	10"	WF-8, 100 yds / 20 lbs	AL	AL	30mm	87mm	50.08	45.07
OKUI1011	10,11 wt.	8.5	1RB	12"	WF-10, 170 yds / 30 lbs	AL	AL	30mm	99mm	50.08	45.07



SIERRA

- Fully adjustable Teflon and stainless drag system
- Precision machined stainless steel spool shafts
- Easy to change left to right hand retrieval conversion

- Roller bearing engages drag in one direction
- ALC: Alumilite diecast aluminum frame design

- Precision machined brass bushing drive system
- Diecast aluminum super large arbor spool design

No.	Line Weight	Weight	Bearings	Line Retrive	Fly Line Cap.	Frame	Spool	Spool Width	Spool Diam.	Price	10% Discount
OKUS45	4,5 wt.	5.3	1RB	8"	WF-4, 105 yds / 12 lbs	AL	AL	17mm	67mm	\$28.62	\$25.76
OKUS56	5,6 wt.	5.3	1RB	9"	WF-5, 160 yds / 20 lbs	AL	AL	20mm	73mm	28.62	25.76
OKUS78	7,8 wt.	5.3	1RB	8"	WF-7, 75 yds / 20 lbs	AL	AL	24mm	67mm	32.19	28.97
OKUS89	8,9 wt.	5.7	1RB	9"	WF-8, 150 yds / 20 lbs	AL	AL	24mm	73mm	32.19	28.97
OKUS1011	10,11 wt.	6.0	1RB	11"	WF-10, 285 yds / 30 lbs	AL	AL	30mm	89mm	39.35	35.42



CASCADE

- Fully adjustable multi-disk drag system
- Super lightweight graphite frame construction

- Roller bearing engages drag in one direction
- Corrosion resistant super large arbor spool design

- Precision machined stainless steel spool shafts
- Easy to change left to right hand retrieval conversion

No.	Line Weight	Weight	Bearings	Line Retrive	Fly Line Cap.	Frame	Spool	Spool Width	Spool Diam.	Price	Discount
OKUCS46	4,5,6 wt.	5.0	1RB	9"	WF-4, 125 yds / 20 lbs	GR	GR	29mm	74mm	\$21.46	\$19.31
OKUCS79	7,8,9 wt.	6.0	1RB	10"	WF-7, 135 yds / 20 lbs	GR	GR	34mm	85mm	21.46	19.31

