

Peel-N-Stick Application Instructions

Recommended for Improved Results

First, Place a coat of epoxy on the blank where you will be placing the decal. Let this dry. **THIS IS VERY IMPORTANT!** The decal will come pre-cut to size with excess decal material removed from it, so there is no need for trimming on your part. The decal itself comes sandwiched between the backing and a top carrier sheet. This allows you to handle the decal without touching its adhesive side.

To apply the decal:

1. lift the carrier sheet from the backing. The decal will come with the top sheet.
2. Place the decal down on the rod in the desired position.
3. Start from the middle and rub the bubbles from there to the edge. You may rub firmly or take a finishing tool and rub over the carrier sheet.
4. We highly suggest you take a heat gun or hair dryer for approx 10-15 seconds over the decal. This is especially important for decals with intricate fin detail.

IMPORTANT
*Once decal is in place, use a hot blow dryer for 10-15 seconds on the decal **BEFORE** removing transfer tape*



5. Then peel the carrier sheet away and the decal remains in place. Your fingers never need to touch the decal because you have the carrier sheet to hold on to it.
6. Once applied, you are ready to apply your finishing coat of epoxy over the decal. Although decals are printed using extremely durable, fade resistant resin ink, applying a clear top coat will enhance the color of the decal and provide additional protection, especially to the edges. It is recommended that **ONLY** a quality two-part epoxy rod finish be used (e.g. FlexCoat, U-40 LS Supreme or similar). **DO NOT USE ACETONE** when mixing epoxy. Do **NOT** apply one-part urethane finishes containing solvents (e.g. U-40 Perma Gloss) directly to the decal. Solvents will ruin the finish on the decal.



C512
DOGFISH



C513
TILEFISH



C514
SEA ROBIN



C515
STING RAY



C516
BUNKER