

BENCHMARK by CUI

| <u>No.</u> | <u>Power</u> | <u>Length</u> | <u>LineWt</u> | <u>Butt Dia</u> | <u>Tip Dia</u> |
|-------------------------------------|---------------|---------------|---------------|-----------------|----------------|
| GRAPHITE CASTING ROD BLANKS | | | | | |
| CUIGC56L | 1 pc Lite | 5'6" | 4-8 | 0.350 | 5.0 |
| CUIGC56M | 1 pc Med. | 5'6" | 6-12 | 0.400 | 5.0 |
| CUIGC60M | 1 pc Med | 6'0" | 6-12 | 0.425 | 5.0 |
| CUIGC60MH | 1 pc Med/Hvy | 6'0" | 8-15 | 0.435 | 5.5 |
| CUIGC60H | 1 pc Hvy | 6'0" | 12-20 | 0.440 | 6.0 |
| CUIGC66M | 1 pc Med. | 6'6" | 6-12 | 0.435 | 5.0 |
| CUIGC66MH | 1 pc Med/Hvy | 6'6" | 8-17 | 0.440 | 5.5 |
| CUIGC66H | 1 pc Hvy | 6'6" | 12-20 | 0.475 | 6.0 |
| CUIGC70ML | 1 pc Med/Lt | 7'0" | 6-12 | 0.435 | 5.0 |
| CUIGC70M | 1 pc Med | 7'0" | 8-15 | 0.450 | 5.5 |
| CUIGC70MH | 1 pc Med/Hvy | 7'0" | 10-20 | 0.485 | 6.0 |
| CUIGC70H | 1 pc Hvy | 7'0" | 15-30 | 0.520 | 6.5 |
| GRAPHITE SPINNING ROD BLANKS | | | | | |
| CUIGS50UL | 1 pc Ult.Lite | 5'0" | 2-6 | 0.290 | 5.0 |
| CUIGS56L | 1 pc Lite | 5'6" | 4-8 | 0.350 | 5.0 |
| CUIGS56M | 1 pc Med | 5'6" | 6-12 | 0.400 | 5.0 |
| CUIGS60L | 1 pc Lite | 6'0" | 4-8 | 0.375 | 5.0 |
| CUIGS60M | 1 pc Med | 6'0" | 6-12 | 0.420 | 5.0 |
| CUIGS60MH | 1 pc Med/Hvy | 6'0" | 8-17 | 0.435 | 5.5 |
| CUIGS66M | 1 pc Med | 6'6" | 6-12 | 0.435 | 5.0 |
| CUIGS66MH | 1 pc Med/Hvy | 6'6" | 8-17 | 0.440 | 5.5 |
| CUIGS70ML | 1 pc Med/Lt | 7'0" | 6-12 | 0.430 | 5.0 |
| CUIGS70M | 1 pc Med | 7'0" | 8-15 | 0.450 | 5.5 |
| CUIGS70MH | 1 pc Med/Hvy | 7'0" | 10-20 | 0.460 | 6.0 |
| CUIGS70H | 1 pc Hvy | 7'0" | 15-30 | 0.500 | 6.5 |

Mid Modullus (36ml)
 unidirectional graphite
 materials provides a
 highly functional
 general purpose
 Graphite Blank.
 Maximum strength and
 sensitivity through
 state-of-the-art
 technology at a
 reasonable cost.